

Coated papers

Toner
Water
(eco) Solvent
UV Curable
Latex

IJM113C Premium Paper - FSC

90 g/m²

Product Description IJM113C is a high-quality matt coated paper recommended for posters and presentation quality CAD and GIS drawings with solid colour fills.

Physical Properties	Weight	90 ± 10 g/m ²	ISO 536	Brightness (R457+)	>95%	ISO 2470
	Thickness	110 ± 10 µm	ISO 534		Tensile strength*	>4,0/1,5 kN/m
Smoothness (Bekk)	100 ± 40 s	ISO 5627	Tearing strength*	>600/600 mN	DIN en ISO 21974	
Opacity	>88%	ISO 2471				

*MD/CD

Applications/Features Colour and monochrome CAD and GIS
High-quality standard and presentation drawings
Indoor Posters
Excellent dot gain and line sharpness
Good contrast
Good smear resistance

Available Widths (mm) 3" Core: 914 1000 1067
Refer for our current offering to mediaguide.oce.com

Storage Conditions Temperature 10°-30° C, Relative Humidity 20-80%.
Repack opened rolls when not in use. Allow material to adapt to room conditions 24 hours before printing.

Print Conditions Best results between 15°-25° C and 30-70% RH.


Environment, Health & Safety No Material Safety Data Sheet required. Waste can be handled as paper waste.

Lamination Compatibility	Cold	Warm	Hot	
	3	3	1	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C - 130°C
	3= excellent 2= fair 1= not recommended			

Outdoor Use This material is not suitable for outdoor use.

Colour Profiles Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on the download section of mediaguide.oce.com

Environmental Certification



you can

Canon

**Processing
Guidelines****Printing guidelines**

Allow material to adapt to room conditions for 24 hours before printing.

It is recommended to handle the media with cotton gloves. Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects.

Insert the paper with care in the printer. Incorrect loading can cause skewing or creasing.

It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer ink combinations.

Ink restrictions and printer settings have to be set for specific printer-ink combinations to obtain the best results. Canon colour profiles will set recommended ink restrictions and printer-settings for Canon supported printers.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

Canon Europe Ltd
3 The Square, Stockley Park
Uxbridge, Middlesex
UB11 1ET UK



English Edition 0214
© Canon Europe N.V., 2014